

Painting Technology Accessories



Small Agitator

Compressed air driven agitator with continuously variable rotation speed and base. Ideal for quick on-site preparation of smaller paint container. Different wavelengths available.



Pneumatic gear agitator

Compressed air operated agitator, very powerful due to gear reduction. Available depending on the application with different agitating vanes and shaft lengths. Optional adapter for drum cover (stainless steel) fixation.



Pressure container

In different sizes, direct filling or for placing paint buckets directly in the container. The paint bucket version is also available with agitator adapter. Operating pressure up to 6 bar, wetted parts in stainless steel (optionally).



Flow heater VULKAN

Maintenance-free, explosion-proof material flow heater for conversion to hot spraying. The application enables higher layer thicknesses, constant material processing parameters at outside temperature fluctuations while saving solvent and working time. Up to 350 bar working pressure.



Hosepacks ND / HD

Available in customized lengths for low pressure and high pressure (air-assisted/airless). Standard connections: 1/4" (air) and M16x1.5 (material), other on request.



Suction/gravity cup sup. device

Combined suction and gravity cup supply device from 4.5 liters gravity cup, suction device with coarse filter and ball valve for two-way switching.



Double gravity cup supply device

Consisting of two 4.5-liter gravity cups and ball valve for two-way switching. Suitable for all established types of equipment, for efficient processing of small quantities.



Single column lifting unit

Pneumatic lifting unit heavy duty, freely rotatable. Lifting height 1000 mm, suitable for drums up to 200 liters. Manufactured from galvanized precision steel tube, with shaft sinking speed regulation.



HD Material pressure agitator

Stainless steel finish. Control range up to 270 bar. Available for three different control pressure ranges. Available in admission pressure and as a back-pressure version.



ND Material pressure agitator

Stainless steel finish. Also available with pneumatic adjustment. Regulation pressure range up to 22 bar. Available for three different control pressure ranges.



HD material filter type 31

High pressure filter for pumps. Stainless steel design, with pressure release device. Pressure range up to 300 bar. Filter inserts are available separately in various sizes.



Air control/maintenance units

For controlling / pretreatment of the supply air pressure of pneumatic equipment. Freely combinable elements such as water separator or fine filters available, various sizes / connections possible.

This brochure shows only a selection from our range of accessories. We will inform you about further additional tools and equipment among 0911 3477-0.



DETE Dr. Tettenborn GmbH
Steinfeldstr. 15.
D-90425 Nürnberg
Tel.: +49 (911) 34 77 0
Fax: +49 (911) 34 77 40
e-mail: dete@dete.de
internet: www.dete.de